


Oceanographic Mooring - Dual Purpose Cage

ASL Dual Mooring Cage for Taut Line Moorings
Including the ASL Ice Profiler in full battery pack
or the TRDI Workhorse ADCP with external battery pack



One of two 3 lbs anodes



Features:

- Specifically designed for the ASL Ice Profiler in a full pressure case or the Workhorse ADCP with external battery pack from Teledyne RDI.
- Shown with the HD modification with max working load of 2,000 lbs (higher loads on request).
- An optional top crown is available for use as an inline cage.
- Overall length is 56" inches (1 420 mm).
- Disassembles for easy and compact shipping.
- 316 stainless steel construction.
- Includes sacrificial anodes for corrosion protection of the cage.
- Cage is electrically isolated from the instrument(s).
- Uses 4, 6 or 8 Viny floats Model 12B3 available upon request.
- Weight in air with anodes but without Viny floats and instrument(s) is only 65 lbs (or 30.kg).
- Est. weight in water with anodes but without Viny floats and instrument(s) is 56 lbs (or 26 kg).

ASL Environmental Sciences

1986 Mills Road, Sidney, BC, Canada V8L 5Y3

Phone: 1-250-656-0177 Fax: 1-250-656-2162 Email: asl@aslenv.com

www.aslenv.com